















We Get Security

End-to-End IP Surveillance Solutions
from D-Link





















Comparison Guide


D-Link's integrated IP surveillance solutions for business provide dependable, high-quality surveillance at a lower overall investment.





D-Link IP Cameras	Cube Cameras			Bullet Cameras			
							
	DCS-2210	DCS-2230	DCS-2310L	DCS-7010L	DCS-7110	DCS-7413	DCS-7513
Resolution	2MP Full HD 1920 x 1080	2MP Full HD 1920 x 1080	1MP HD 1280 x 720	1MP HD 1280 x 800	1MP HD 1280 x 800	2MP Full HD 1920 x 1080	2MP Full HD 1920 x 1080
Lens	4.37mm F2.0 Fixed Iris	4.37mm F2.0 Fixed Iris	3.45mm F2.0 Fixed Iris	4.3mm F2.0 Fixed Iris	4mm F1.5 Fixed Iris	4.3mm F2.0 Fixed Iris	3-9mm F1.2 Motorized P-Iris
Horizontal Field of View	67° 	67° 	58° 	74° 	65° 	74° 	121°-38° 
Sensor	1/2.7" CMOS	1/2.7" CMOS	1/4" CMOS	1/4" CMOS	1/4" CMOS	1/2.7" CMOS	1/2.8" CMOS Sony Exmor
LUX Rating	1 Lux (Color) 0 Lux (IR LED)	1 Lux (Color) 0 Lux (IR LED)	1 Lux (Color) 0 Lux (IR LED)	1 Lux (Color) 0 Lux (IR LED)	0.26 Lux (Color) 0 Lux (IR LED)	0.26 Lux (Color) 0 Lux (IR LED)	0.02 Lux (Color) 0.05 Lux (B/W) 0 Lux (IR LED)
Wide Dynamic Range (WDR)							✓
Day & Night	✓	✓	✓	✓	✓	✓	✓
Integrated Illumination	Infrared (15 ft)	Infrared (15 ft)	Infrared (15 ft)	Infrared (30 ft)	Infrared (45 ft)	Infrared (90 ft)	Infrared (90 ft)
Frames per Second	30 (1280 x 720) 15 (1920 x 1080)	30 (1280 x 720) 15 (1920 x 1080)	30	30	30	30 (1280 x 720) 15 (1920 x 1080)	30
Video Compression	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile
Audio Support	2-Way Built-in Mic Built-in Speaker	2-Way Built-in Mic Built-in Speaker	2-Way Built-in Mic Built-in Speaker	2-Way		2-Way	2-Way
Alarm In/Out	1/1	1/1		1/1	1/1	1/1	1/1
Intelligent Video	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection
Onvif Support	✓	✓	✓	✓	✓	✓	✓
Monitor Output						✓	✓
Security	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS
Local Storage	microSD Card Slot	microSD Card Slot	microSD Card Slot	microSD Card Slot		SD Card Slot	SD Card Slot
Power	PoE / 5VDC 3.5W	5VDC 4W	PoE / 5VDC 5.3W	PoE / 5VDC 5.4W	PoE / 12VDC 6W	PoE / 12VDC 24VAC 11.2W	PoE / 12VDC 24VAC 11W
Outdoor Use	No	No	Yes (IP65)	Yes (IP66)	Yes (IP66)	Yes (IP66)	Yes (IP66)
Other	PIR Sensor Mount Included	Wireless N PIR Sensor Mount Included	PIR Sensor Mount Included -13° to 113° F	Mount Included Cloud-Enabled -13°F to 122°F	Mount Included -4° to 122°F	Vandalproof Cable Management Mount Included -40° to 122° F	Vandalproof Cable Management Mount Included -40° to 122° F
Warranty	1-Year	1-Year	1-Year	1-Year	5-Year	5-Year	5-Year
MSRP	\$324.99	\$324.99	\$389.99	\$389.99	\$599.99	\$749.99	\$1,069.99










Zoom in on our lineup and you'll discover full-featured cameras that deliver the very latest technology. Our lineup includes onboard video processing, motion and tamper detection, high definition and multi-megapixel resolution, ICR for recording in any light and more.



D-Link IP Cameras	Dome Cameras (Indoor)				Dome Cameras (Outdoor)				
									
	DCS-6010L	DCS-6111	DCS-6112	DCS-6113	DCS-6210	DCS-6314	DCS-6510	DCS-6511	DCS-6513
Resolution	2MP 1600 x 1200	VGA 640 X 480	2MP Full HD 1920 x 1080	2MP Full HD 1920 x 1080	2MP Full HD 1920 x 1080	2MP Full HD 1920 x 1080	VGA 640 X 480	1.3MP HD 1280 x 1024	3MP Full HD 2048 x 1536
Lens	1.25mm F2.0 Fixed Iris	3.3-12MM F1.4 Varifocal Auto Iris	4mm F1.5 Fixed Iris	4mm F1.5 Fixed Iris	4.3mm F2.0 Fixed Iris	2.8-12mm F1.4 Varifocal Auto Iris	3.7-12MM F1.4 Varifocal Auto Iris	3.3-12mm F1.4 Motorized Auto Iris	3-9mm F1.2 Motorized P-Iris
Horizontal Field of View	180° 	63°-18° 	77° 	77° 	79° 	97°-31° 	77°-23° 	90°-24° 	96°-32° 
Sensor	1/3.2" CMOS	1/4" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.8" CMOS	1/4" CMOS	1/3" CMOS	1/2.8" CMOS Sony Exmor
LUX Rating	2 Lux	1.5 Lux (Color) 0 Lux (IR LED)	0.12 Lux	0.12 Lux (Color) 0 Lux (IR LED)	1 Lux	0.2 Lux (Color) 0.05 Lux (B/W) 0 Lux (IR LED)	0.2 Lux (Color) 0.02 Lux (B/W) 0 Lux (IR LED)	0.2 Lux 0.05 Lux (B/W) 0 Lux (IR LED)	0.5 Lux (Color) 0.05 Lux (B/W)
Wide Dynamic Range (WDR)		✓				✓		✓	✓
Day & Night		✓		✓		✓	✓	✓	✓
Integrated Illumination		Infrared (60 ft)		Infrared (30 ft)		Infrared (45 ft)	Infrared (60 ft)	Infrared (60 ft)	Infrared (60 ft)
Frames per Second	15	30	30 (1280 x 720) 15 (1920 x 1080)	30 (1280 x 720) 15 (1920 x 1080)	30 (1280 x 720) 15 (1920 x 1080)	30	30	30	30 (1920 x 1080) 15 (2048 x 1536)
Video Compression	H.264 MPEG-4 MJPEG Multi-Profile	MPEG-4 MJPEG	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile
Audio Support	2-Way Built-in Mic Built-in Speaker	2-Way	2-Way	2-Way	1-Way Built-in Mic	2-Way	2-Way	2-Way	2-Way
Alarm In/Out		1/1	1/1	1/1		1/1	1/1	1/1	1/1
Intelligent Video	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection
Onvif Support	✓		✓	✓	✓	✓	✓	✓	✓
Monitor Output			✓	✓		✓	✓	✓	✓
Security	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS
Local Storage	microSD Card Slot		microSD Card Slot	microSD Card Slot	microSD Card Slot	microSD Card Slot	SD Card Slot	SD Card Slot	SD Card Slot
Power	5VDC 3.9W	PoE / 12VDC 11W	PoE / 12VDC 4W	PoE / 12VDC 5.3W	PoE / 12VDC 8.6W	PoE / 12VDC 10W	PoE / 12VDC 11W	PoE / 12VDC 24VAC 9W	PoE / 12VDC 24VAC 10.5W
Outdoor Use	No	No	No	No	Yes (IP66)	Yes (IP68)	Yes (IP66)	Yes (IP66)	Yes (IP66)
Other	360° / 180° Wireless N				Compact Vandalproof -13° to 122° F	Weather Guard Vandalproof -22° to 122° F	Vandalproof -4° to 122° F	Vandalproof -40° to 122° F	Weather Guard Vandalproof -40° to 122° F
Warranty	1-Year	5-Year	5-Year	5-Year	5-Year	5-Year	5-Year	5-Year	5-Year
MSRP	\$389.99	\$319.99	\$479.99	\$519.99	\$499.99	\$649.99	\$469.99	\$999.99	\$1,199.99

Regardless of your customers' unique physical environments, you can trust that end-to-end IP surveillance solutions from D-Link will ensure security. D-Link Gets Security.

D-Link IP Cameras	Box Cameras				PTZ & Speed Dome Cameras				
									
	DCS-3010	DCS-3112	DCS-3710	DCS-3716	DCS-5605	DCS-5635	DCS-6616	DCS-6818	DCS-6915
Resolution	1MP HD 1280 x 800	1.3MP HD 1280 x 1024	1.3MP HD 1280 x 1024	3MP Full HD 2048 x 1536	D1 720 x 480	D1 720 x 480	D1 720 x 480	D1 720 x 480	2MP Full HD 1920 x 1080
Lens	4mm F1.5 Fixed Iris	3.5-8mm F1.4 Varifocal Auto Iris CS-Mount	2.9-8.2mm F1.0 Varifocal Auto Iris CS-Mount	3.1-8mm F1.2 Varifocal Auto Iris CS-Mount	3.8-38mm F1.8 10x Zoom	3.8-38mm F1.8 10x Zoom	3.8 to 45.6mm F1.6 12x Zoom	3.4-122.4mm F1.4 36x Zoom	4.7-96mm F1.6 20x Zoom
Horizontal Field of View	57° 	78°-35° 	95°-36° 	96°-39° 	51°-6° 	51°-6° 	53°-4.5° 	61°-1.8° 	52°-4° 
Sensor	1/4" CMOS	1/4" CMOS	1/3" CMOS Sony Exmor	1/2.8" CMOS Sony Exmor	1/3" CCD	1/3" CCD	1/4" CCD Sony Super HAD-II	1/4" CCD Sony Exview	1/2.8" CMOS Sony Exmor
LUX Rating	1 Lux	0.4 Lux (Color) 0.04 Lux (B/W)	0.2 Lux (Color) 0.02 Lux (B/W)	0.5 Lux (Color) 0.05 Lux (B/W)	0.7 Lux (Color) 0.02 Lux (B/W)	0.7 Lux (Color) 0.02 Lux (B/W)	0.1 Lux (Color) 0.01 Lux (B/W)	0.1 Lux (Color) 0.01 Lux (B/W)	0.1 Lux (Color) 0.01 Lux (B/W) 0 Lux (IR LED)
Wide Dynamic Range (WDR)			✓	✓			✓	✓	✓
Day & Night		✓	✓	✓	✓	✓	✓	✓	✓
Integrated Illumination									
Frames per Second	30	30	30	30 (1920 x 1080) 15 (2048 x 1536)	30	30	30	30	30
Video Compression	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 Multi-Profile
Audio Support	2-Way	2-Way	2-Way	2-Way	2-Way Built-in Mic	2-Way Built-in Mic	2-Way		2-Way
Alarm In/Out		2/1	2/1	2/1	1/1	1/1	8/1	8/1	4/2
Intelligent Video	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection
Onvif Support	✓	✓	✓	✓			✓	✓	✓
Monitor Output		✓	✓	✓	✓	✓	✓	✓	
Security	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password	Multi-Level Password	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS
Local Storage	microSD Card Slot	SD Card Slot	SD Card Slot	SD Card Slot	microSD Card Slot	microSD Card Slot			SD Card Slot
Power	PoE / 12VDC 4.6W	PoE / 12VDC 3.6W	PoE / 12VDC 3.8W	PoE / 12VDC 3.8W	PoE / 12VDC 12W	12VDC 13.4W	12VDC 14W	24VAC 65W	24VDC 65W
Outdoor Use	With Enclosure	With Enclosure	With Enclosure	With Enclosure	With DCS-71P Enclosure	With DCS-71W Enclosure	No	Yes (IP66)	Yes (IP66)
Other	Lens Included Mount Included	Lens Included Mount Included	Lens Included Mount Included	Lens Included Mount Included		Wireless N	Endless 360° Pan 400°/Second	Endless 360° Pan 400°/Second -40° to 122° F	Endless 360° Pan 400°/Second -40° to 122° F
Warranty	5-Year	5-Year	5-Year	5-Year	1-Year	1-Year	1-Year	1-Year	1-Year
MSRP	\$269.99	\$619.99	\$829.99	\$946.99	\$1,099.99	\$1,199.99	\$1,239.99	\$2,499.99	\$2,999.99

D-Link Enclosures	Box Camera Enclosure	PTZ Enclosures		Outdoor Power Supply
				
	DCS-55	DCS-71P	DCS-71W	DCS-80-5
IP Rating	IP66	IP66	IP66	IP66
Input Power	PoE 802.3at	PoE 802.3at	24VAC	100-115VAC
Output Power	12VDC	12VDC or PoE 802.3af	12VDC	24VAC
Temperature Range	-22° to 140° F (-30° to 60° C)	-4° to 113° F (-20° to 45° C)	-4° to 113° F (-20° to 45° C)	-40° to 122° F
Supported Cameras	All D-Link Box Cameras	DCS-5605	DCS-5635	DCS-6511, DCS-6818, DCS-71W
Notes	Wall Mount Included	Wall Mount Included	Wall Mount Included	

Mounts	Mounts								
									
	DCS-32-2	DCS-32-4	DCS-33-1	DCS-33-2	DCS-33-3	DCS-33-4	DCS-34-2	DCS-34-3	DCS-35-1
Description	Long Pendant Mount	Mini Wall Mount	Flush Mount	Surface Mount	Pendant Mount	Wall Mount	Pendant Mount	Wall Mount	Flush Mount
Supported Cameras	DCS-6818 DCS-6915	DCS-6818 DCS-6915	DCS-6510	DCS-6510	DCS-6510	DCS-6510	DCS-6314 DCS-6511 DCS-6513	DCS-6314 DCS-6511 DCS-6513	DCS-6616

Network Video Recorders	Network Video Recorders	
		
	DNR-322L	DNR-326
Supported IP Cameras	D-Link	D-Link, Axis, Panasonic, Sony, Mobotix, Arecont Vision, IQinVision, Cisco and ACTi
Channels	9	9
Recording Performance	Up to 270 FPS @ HD (1280 x 720)	Up to 270 FPS @ HD (1280 x 720)
Record on Camera Motion Detection	✓	✓
HDD Bays	2 x 3.5" SATA	2 x 3.5" SATA
Max Capacity	6TB	6TB
Network	1x GigE LAN Port	1x GigE LAN Port
Raid Levels	Single, RAID 0, RAID 1, JBOD	Single, RAID 0, RAID 1, JBOD
mylink Cloud Enabled	✓	
Supported Compression	H.264 MPEG4 MJPEG	H.264 MPEG4 MJPEG
Auto Camera Detection	✓	✓
Digital Input/Output		1/1
Smart Search		✓
Multiple NVR Management/Viewing Client Software		✓
MSRP	\$299.99	\$649.99

Video Management Software (VMS)



Each D-Link IP camera includes a free 32-camera VMS solution called D-ViewCam. If your customer's surveillance needs require a more robust, full featured and scalable solution, D-Link has a large number of VMS partners that support D-Link's line of IP cameras.

Virtually all D-Link cameras are Onvif-compliant, enabling IP cameras, NVRs and VMS solutions from multiple vendors to seamlessly work together.





Comprehensive Service and Support

D-Link Professional Services and Support for business ensures you get the best fit solution for your unique environment.

Call or visit us online for more information on the complete line of D-Link IP Surveillance solutions

ipsurveillance.dlink.com

888.331.8686 | Email: getmore@dlink.com