

# IP SURVEILLANCE

















Comparison Guide

**D-Link**<sup>®</sup>  
FOR BUSINESS





















# Comparison Guide















D-Link's integrated IP surveillance solutions for business provide dependable, high-quality surveillance at a lower overall investment.



D-Link IP Cameras	Cube Cameras				Bullet Cameras			
								
	DCS-2136L	DCS-2210	DCS-2230	DCS-2310L	DCS-7010L	DCS-7110	DCS-7413	DCS-7513
Resolution	1280 x 800	2MP Full HD 1920 x 1080	2MP Full HD 1920 x 1080	1MP HD 1280 x 720	1MP HD 1280 x 800	2MP HD 1920 x 1080	2MP Full HD 1920 x 1080	2MP Full HD 1920 x 1080
Lens	3.6mm F1.4	4.37mm F2.0	4.37mm F2.0	3.45mm F2.0	3.6mm F1.8	4mm F1.5	3.6mm F1.8	3-9mm F1.2 Motorized P-Iris
Horizontal Field of View	64° 	67° 	67° 	58° 	58° 	77° 	88° 	121°-38' 
Sensor	1/3" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/4" CMOS	1/4" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.8" CMOS Sony Exmor
LUX Rating	0.1 Lux (Color) 0 Lux (Visible LED)	1 Lux (Color) 0 Lux (IR LED)	1 Lux (Color) 0 Lux (IR LED)	1 Lux (Color) 0 Lux (IR LED)	1 Lux (Color) 0 Lux (IR LED)	0.12 Lux (Color) 0 Lux (IR LED)	0.26 Lux (Color) 0 Lux (IR LED)	0.02 Lux (Color) 0.05 Lux (B/W) 0 Lux (IR LED)
Wide Dynamic Range (WDR)	✓							✓
Day & Night	✓	✓	✓	✓	✓	✓	✓	✓
Integrated IR LEDs	White Light (15 ft)	Infrared (15 ft)	Infrared (15 ft)	Infrared (15 ft)	Infrared (30 ft)	Infrared (45 ft)	Infrared (90 ft)	Infrared (90 ft)
Frames per Second	30	30 (1280 x 720) 15 (1920 x 1080)	30 (1280 x 720) 15 (1920 x 1080)	30	30	30 (1280 x 720) 15 (1920 x 1080)	30	30
Video Compression	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile
Audio Support	2-Way Built-in Mic Built-in Speaker	2-Way Built-in Mic Built-in Speaker	2-Way Built-in Mic Built-in Speaker	2-Way Built-in Mic Built-in Speaker	2-Way		2-Way	2-Way
Alarm In/Out	1/1	1/1	1/1		1/1	1/1	1/1	1/1
Intelligent Video	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection
Onvif Support	✓	✓	✓	✓	✓	✓	✓	✓
Monitor Output							✓	✓
Security	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS
Local Storage	microSD Card Slot	microSD Card Slot	microSD Card Slot	microSD Card Slot	microSD Card Slot		SD Card Slot	SD Card Slot
Power	5VDC 4W	PoE / 5VDC 3.5W	5VDC 4W	PoE / 5VDC 5.3W	PoE / 5VDC 8.8W	PoE / 12VDC 6W	PoE / 12VDC 24VAC 11.2W	PoE / 12VDC 24VAC 11W
Outdoor Use	No	No	No	Yes (IP65)	Yes (IP66)	Yes (IP66)	Yes (IP68)	Yes (IP66)
Other	White Light LED Wireless AC PIR Sensor Mount Included	PIR Sensor Mount Included	Wireless N PIR Sensor Mount Included	PIR Sensor Mount Included -13° to 113° F	Mount Included Cloud-Enabled -13°F to 122°F	Tamper Detection Mount Included -4° to 122° F	Vandalproof Cable Management Mount Included -40° to 122° F	Vandalproof Cable Management Mount Included -40° to 122° F
Warranty	1-Year	1-Year	1-Year	1-Year	1-Year	5-Year	5-Year	5-Year
MSRP	\$324.99	\$279.99	\$279.99	\$389.99	\$359.99	\$519.99	\$749.99	\$1,069.99




Zoom in on our lineup and you'll discover full-featured cameras that deliver the very latest technology. Our lineup includes onboard video processing, motion and tamper detection, high definition and multi-megapixel resolution, ICR for recording in any light and more.








D-Link IP Cameras	Indoor Dome Cameras				Outdoor Dome Cameras				
									
	DCS-6004L	DCS-6010L	DCS-6112	DCS-6113	DCS-6210	DCS-6314	DCS-6315	DCS-6511	DCS-6513
Resolution	1MP HD 1280 x 800	2MP 1600 x 1200	2MP Full HD 1920 x 1080	2MP Full HD 1920 x 1080	2MP Full HD 1920 x 1080	2MP Full HD 1920 x 1080	1MP HD 1280 x 720	1.3MP HD 1280 x 1024	3MP Full HD 2048 x 1536
Lens	2.8mm F1.8	1.25mm F2.0	4mm F1.5	4mm F1.5	3.6mm F1.8	2.8-12mm F1.4 Varifocal Auto Iris	2.8-12mm F1.4 Varifocal Auto Iris	3.3-12mm F1.4 Motorized	3-9mm F1.2 Motorized P-Iris
Horizontal Field of View	75° 	180° 	77° 	77° 	88° 	97°-31° 	90°-28° 	96°-32° 	90°-24° 
Sensor	1/4" CMOS	1/3.2" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.8" CMOS	1/3" CMOS	1/3" CMOS	1/2.8" CMOS Sony Exmor
LUX Rating	0.5 Lux (Color) 0 Lux (IR LED)	2 Lux	0.12 Lux	0.12 Lux (Color) 0 Lux (IR LED)	1 Lux	0.2 Lux (Color) 0.05 Lux (B/W) 0 Lux (IR LED)	0.1 Lux (Color) 0.02 Lux (B/W) 0 Lux (IR LED)	0.2 Lux 0.05 Lux (B/W) 0 Lux (IR LED)	0.5 Lux (Color) 0.05 Lux (B/W) 0 Lux (IR LED)
Wide Dynamic Range (WDR)						✓	✓	✓	✓
Day & Night	✓			✓		✓	✓	✓	✓
Integrated IR LEDs	Infrared (15 ft)			Infrared (45 ft)		Infrared (45 ft)	Infrared (45 ft)	Infrared (60 ft)	Infrared (60 ft)
Frames per Second	30	15	30	30	30 (1280 x 720) 15 (1920 x 1080)	30	30	30	30 (1920 x 1080) 15 (2048 x 1536)
Video Compression	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile
Audio Support	2-Way Built-in Mic	2-Way Built-in Mic Built-in Speaker	2-Way	2-Way	1-Way Built-in Mic	2-Way	2-Way	2-Way	2-Way
Alarm In/Out			1/1	1/1		1/1	1/1	1/1	1/1
Intelligent Video	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection
Onvif Support	✓	✓	✓	✓	✓	✓	✓	✓	✓
Monitor Output			✓	✓		✓		✓	✓
Security	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS
Local Storage	microSD Card Slot	microSD Card Slot	microSD Card Slot	microSD Card Slot	microSD Card Slot	microSD Card Slot	microSD Card Slot	SD Card Slot	SD Card Slot
Power	PoE / 12VDC 3.5W	5VDC 3.9W	PoE / 12VDC 4W	PoE / 12VDC 5.3W	PoE / 12VDC 8.6W	PoE / 12VDC 10W	PoE / 12VDC 12.5W	PoE / 12VDC 24VAC 9W	PoE / 12VDC 24VAC 10.5W
Outdoor Use	No	No	No	No	Yes (IP68)	Yes (IP68)	Yes (IP68)	Yes (IP66)	Yes (IP67)
Other	Includes White & Black Case Options	360° / 180° Wireless N			Compact Vandalproof -13° to 122° F	Weather Guard Vandalproof -13° to 122° F	Weather Guard Vandalproof -13° to 122° F	Vandalproof -40° to 122° F	Weather Guard Vandalproof -40° to 122° F
Warranty	1-Year	1-Year	5-Year	5-Year	5-Year	5-Year	5-Year	5-Year	5-Year
MSRP	\$289.99	\$389.99	\$414.99	\$444.99	\$409.99	\$659.99	\$649.99	\$849.99	\$1,019.99

Regardless of your customers' unique physical environments, you can trust that end-to-end IP surveillance solutions from D-Link will ensure security. D-Link Gets Security.

D-Link IP Cameras	Box Cameras			Pan/Tilt & Speed Dome Cameras			
							
	DCS-3010	DCS-3710	DCS-3716	DCS-5615	DCS-6616	DCS-6818	DCS-6915
Resolution	1MP HD 1280 x 800	1.3MP HD 1280 x 1024	3MP Full HD 2048 x 1536	2MP Full HD 1920 x 1080	D1 720 x 480	D1 720 x 480	2MP Full HD 1920 x 1080
Lens	4mm F1.5 CS-Mount	2.9-8.2mm F1.0 Varifocal Auto Iris CS-Mount	3.1-8mm F1.2 Varifocal Auto Iris CS-Mount	4mm F1.5	3.8 to 45.6mm F1.6 12x Zoom	3.4-122.4mm F1.4 36x Zoom	4.7-96mm F1.6 20x Zoom
Horizontal Field of View	57° 	78°-35° 	96°-39° 	77° 	53°-4.5° 	61°-1.8° 	52°-4° 
Sensor	1/4" CMOS	1/3" CMOS Sony Exmor	1/2.8" CMOS Sony Exmor	1/2.7" CMOS	1/4" CCD Sony Super HAD-II	1/4" CCD Sony Exview	1/2.8" CMOS Sony Exmor
LUX Rating	1 Lux	0.2 Lux (Color) 0.02 Lux (B/W)	0.5 Lux (Color) 0.05 Lux (B/W)	0.12 Lux	0.1 Lux (Color) 0.01 Lux (B/W)	0.1 Lux (Color) 0.01 Lux (B/W)	0.1 Lux (Color) 0.01 Lux (B/W)
Wide Dynamic Range (WDR)		✓	✓		✓	✓	✓
Day & Night		✓	✓		✓	✓	✓
Integrated IR LEDs							
Frames per Second	30	30	30 (1920 x 1080) 15 (2048 x 1536)	30 (1280 x 720) 15 (1920 x 1080)	30	30	30
Video Compression	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MJPEG Multi-Profile
Audio Support	2-Way	2-Way	2-Way	1-Way Built-in Mic	2-Way		2-Way
Alarm In/Out		2/1	2/1	1	8/1	8/1	4/2
Intelligent Video	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection
Onvif Support	✓	✓	✓	✓	✓	✓	✓
Monitor Output		✓	✓		✓	✓	
Security	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS
Local Storage	microSD Card Slot	SD Card Slot	SD Card Slot	microSD Card Slot			SD Card Slot
Power	PoE / 12VDC 3W	PoE / 12VDC 3.8W	PoE / 12VDC 3.8W	PoE / 12VDC 5.8W	12VDC 14W	24VAC 65W	24VAC 65W
Outdoor Use	With Enclosure	With Enclosure	With Enclosure	No	No	Yes (IP66)	Yes (IP66)
Other	Lens Included Mount Included	Lens Included Mount Included	Lens Included Mount Included	360° Pan Range (-180° to +180°) 80° Tilt Range	Endless 360° Pan 400°/Second	Endless 360° Pan 400°/Second -40° to 122° F	Endless 360° Pan 400°/Second -40° to 122° F
Warranty	5-Year	5-Year	5-Year	1-Year	1-Year	1-Year	1-Year
MSRP	\$244.99	\$529.99	\$759.99	\$479.99	\$1,049.99	\$2,119.99	\$2,499.99

D-Link Enclosures & Power Supplies	Box Camera Enclosure	Outdoor Power Supply
		
	DCS-57	DCS-80-5
IP Rating	IP66	IP66
Input Power	PoE 802.3at	100-115VAC
Output Power	PoE or 12VDC	24VAC
Temperature Range	-40° to 122° F	-40° to 122° F
Supported Cameras	D-Link Box Cameras	DCS-6818, DCS-6915
Notes	Requires DCS-36-1 Wall Mount or DCS-36-2 Roof Mount	

Network Video Recorders	Network Video Recorders		
			
	DNR-312L	DNR-322L	DNR-326
Supported IP Cameras	D-Link	D-Link	D-Link, Axis, Panasonic, Sony, Mobotix, Arecont Vision, IQinVision, Cisco and ACTi
Channels	9	9	9
Recording Performance	Up to 270 FPS @ HD	Up to 270 FPS @ HD (1280 x 720)	Up to 270 FPS @ HD (1280 x 720)
Record on Camera Motion Detection	✓	✓	✓
HDD Bays	1 x 3.5" SATA	2 x 3.5" SATA	2 x 3.5" SATA
Max Capacity	6TB	12TB	12TB
Network	1x GigE LAN Port	1x GigE LAN Port	1x GigE LAN Port
Raid Levels	N/A	Single, RAID 0, RAID 1, JBOD	Single, RAID 0, RAID 1, JBOD
mydlink Cloud Enabled	✓	✓	
Supported Compression	H.264, MPEG-4 MJPEG	H.264 MPEG-4 MJPEG	H.264 MPEG-4 MJPEG
Auto Camera Detection	✓	✓	✓
Digital Input/Output			1/1
HMDI Out, Mouse In	✓		
Smart Search			✓
Multiple NVR Management/Viewing Client Software	✓	✓	✓
MSRP	\$349.99	\$254.99	\$549.99

Mounts	Mounts						
							
	DCS-32-2	DCS-32-4	DCS-34-2	DCS-34-3	DCS-35-1	DCS-36-1	DCS-36-2
Description	Pendant Mount	Wall Mount	Pendant Mount	Wall Mount	Flush Mount	Wall Mount	Roof/Ceiling Mount
Supported Products	DCS-6818, DCS-6915	DCS-6818, DCS-6915	DCS-6314, DCS-6315, DCS-6511, DCS-6513	DCS-6314, DCS-6315, DCS-6511, DCS-6513	DCS-6616	DCS-57	DCS-57



Each D-Link IP camera includes a free 32-camera VMS solution called D-ViewCam. If your customer's surveillance needs require a more robust, full featured and scalable solution, D-Link has a large number of VMS partners that support D-Link's line of IP cameras.

Virtually all D-Link cameras are Onvif-compliant, enabling IP cameras, NVRs and VMS solutions from multiple vendors to seamlessly work together.





## Comprehensive Service and Support

D-Link Professional Services and Support for business ensures you get the best fit solution for your unique environment.

Call or visit us online for more information on the complete line of D-Link IP Surveillance solutions

[ipsurveillance.dlink.com](http://ipsurveillance.dlink.com)

888.331.8686 | Email: [getmore@dlink.com](mailto:getmore@dlink.com)