



















IP SURVEILLANCE

Comparison Guide

D-Link[®]
FOR BUSINESS

















Zoom in on our lineup and you'll discover full-featured cameras that deliver the very latest technology. Our lineup includes onboard video processing, motion and tamper detection, high definition and multi-megapixel resolution, ICR for recording in any light, and more.



D-Link IP Cameras	Vigilance Line						Bullet Cameras		
									
Resolution	2MP Full HD 1920 x 1080	3MP Full HD 2048 x 1536	3MP Full HD 1920 x 1536	1MP HD 1280 x 800	3MP Full HD 2048 x 1536	2MP Full HD 1920 x 1080	1MP HD 1280 x 800	2MP Full HD 1920 x 1080	5MP Full HD 2592 x 1944
Lens	2.8mm F1.8	2.8mm F2.0	1.1mm F2.0	2.8mm F1.8	3.6mm F1.8	2.8mm F1.8	3.6mm F1.8	2.8-12mm F1.4 Motorized Varifocal	2.8-12mm F1.4 Motorized Varifocal
Horizontal Field of View	96° 	84° 	180° 	96° 	70° 	96° 	58° 	108°-33° 	75°-24° 
Sensor	1/3" CMOS	1/3" CMOS	1/3" CMOS	1/3" CMOS	1/3" CMOS	1/3" CMOS	1/4" CMOS	1/2.8" CMOS	1/2.9" CMOS
LUX Rating	1 Lux (Color) 0.5 Lux (B/W) 0 Lux (IR LED)	0.5 Lux (Color) 0.25 Lux (B/W) 0 Lux (IR LED)	0.5 Lux (Color) 0.25 Lux (B/W) 0 Lux (IR LED)	0.2 Lux (Color) 0.1 Lux (B/W) 0 Lux (IR LED)	0.2 Lux (Color) 0.1 Lux (B/W) 0 Lux (IR LED)	1 Lux (Color) 0.5 Lux (B/W) 0 Lux (IR LED)	1 Lux (Color) 0 Lux (IR LED)	0.01 Lux (Color) 0.008 Lux (B/W) 0 Lux (IR LED)	0.01 Lux (Color) 0.008 Lux (B/W) 0 Lux (IR LED)
Wide Dynamic Range (WDR)	Digital WDR	Digital WDR	Digital WDR	Digital WDR	Digital WDR	Digital WDR		Digital WDR	Digital WDR
Day & Night	✓	✓	✓	✓	✓	✓	✓	✓	✓
Integrated Illumination	Infrared (65 ft)	Infrared (32 ft)	Infrared (25 ft)	Infrared (98 ft)	Infrared (65 ft)	Infrared (65 ft)	Infrared (30 ft)	Smart IR-LED (98 ft)	Smart IR-LED (98 ft)
Frames per Second	30	30 (1920 x 1080) 15 (2048 x 1536)	25	30	30 (1920 x 1080) 15 (2048 x 1536)	30	30	60 (WDR On) 30 (WDR Off)	30
Video Compression	H.264 MJPEG Multi-Profile	H.264 MJPEG Multi-Profile	H.264 MJPEG Multi-Profile	H.264 MJPEG Multi-Profile	H.264 MJPEG Multi-Profile	H.264 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MJPEG Multi-Profile	H.265 H.264 MJPEG Multi-Profile
Audio Support			2-Way Built-in Mic Built-in Speaker				2-Way	2-Way	2-Way
Alarm In/Out							1/1	1/1	1/1
Intelligent Video	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection
Onvif Support	✓	✓	✓	✓	✓	✓	✓	✓	✓
Monitor Output								✓	✓
Security	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS
Local Storage			microSD Card Slot				microSD Card Slot	microSD Card Slot	microSD Card Slot
Power	PoE / 12VDC 5.5W	PoE / 12VDC 4.2W	PoE / 12VDC 4.6W	PoE / 12VDC 4.7W	PoE / 12VDC 6.4W	PoE / 12VDC 5.2W	PoE / 5VDC 7W	PoE / 12VDC 10W	PoE / 12VDC 10W
Positioning	2-Axis	3-Axis	N/A (Tilt Only - 15°)	3-Axis	3-Axis	3-Axis	3-Axis	2-Axis	3-Axis
Outdoor Use	Yes (IP66)	No	No	Yes (IP66)	Yes (IP66)	Yes (IP66)	Yes (IP66)	Yes (IP68)	Yes (IP68)
Other	Compact Vandalproof -22° to 122° F	Compact 3D Filter	Compact 3D Filter	Compact -22° to 122° F	Compact -22° to 122° F 3D Filter	Compact -22° to 122° F	Mount Included Cloud-Enabled -13° to 122° F	Mount Included -40° to 122° F	Cable Management Mount Included -40° to 122° F
Warranty	5-Year	5-Year	5-Year	5-Year	5-Year	5-Year	1-Year	5-Year	5-Year
Pricing*	\$	\$	\$	\$	\$	\$	\$\$	\$\$\$	\$\$\$

*Pricing Legend: Value = \$, Mid-Tier = \$\$, High-End = \$\$\$



Regardless of your customers' unique physical environments, you can trust that end-to-end IP surveillance solutions from D-Link will ensure security. D-Link Gets Security.

D-Link IP Cameras	Dome Cameras						Pan/Tilt & Speed Dome Camera
							
	DCS-6010L	DCS-6212L	DCS-6314	DCS-6315	DCS-6513	DCS-6517	DCS-6616
Resolution	2MP 1600 x 1200	2MP Full HD 1920 x 1080	2MP Full HD 1920 x 1080	1MP HD 1280 x 720	3MP Full HD 2048 x 1536	5MP Full HD 2592 x 1944	D1 720 x 480
Lens	1.25mm F2.0	2.8mm F2.0	2.8-12mm F1.4 Varifocal Auto Iris	2.8-12mm F1.4 Varifocal Auto Iris	3-9mm F1.2 Motorized P-Iris	2.8-12mm F1.4 Motorized Varifocal	3.8 to 45.6mm F1.6 12x Zoom
Horizontal Field of View	180° 	84° 	97°-31° 	90°-28° 	108°-33° 	75°-24° 	53°-4.5° 
Sensor	1/3.2" CMOS	1/3" CMOS	1/2.8" CMOS	1/3" CMOS	1/2.8" CMOS Sony Exmor	1/2.9" CMOS	1/4" CCD Sony Super HAD-II
LUX Rating	2 Lux	0.1 Lux (Color) 0.5 Lux (B/W) 0 Lux (IR LED)	0.2 Lux (Color) 0.05 Lux (B/W) 0 Lux (IR LED)	0.1 Lux (Color) 0.02 Lux (B/W) 0 Lux (IR LED)	0.5 Lux (Color) 0.05 Lux (B/W) 0 Lux (IR LED)	0.01 Lux (Color) 0.008 Lux (B/W) 0 Lux (IR LED)	0.1 Lux (Color) 0.01 Lux (B/W)
Wide Dynamic Range (WDR)			✓	✓	✓	Digital WDR	✓
Day & Night		✓	✓	✓	✓	✓	✓
Integrated Illumination		Infrared (32 ft)	Infrared (49 ft)	Infrared (49 ft)	Infrared (65 ft)	Smart IR-LED (65 ft)	
Frames per Second	15	30	30	30	30 (1920 x 1080) 15 (2048 x 1536)	30	30
Video Compression	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile	H.265 H.264 MJPEG Multi-Profile	H.264 MPEG-4 MJPEG Multi-Profile
Audio Support	2-Way Built-in Mic Built-in Speaker	2-Way Built-in Mic Built-in Speaker	2-Way	2-Way	2-Way	2-Way	2-Way
Alarm In/Out			1/1	1/1	1/1	1/1	8/1
Intelligent Video	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection	Motion Detection
Onvif Support	✓	✓	✓	✓	✓	✓	✓
Monitor Output					✓	✓	✓
Security	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS	Multi-Level Password HTTPS
Local Storage	microSD Card Slot	microSD Card Slot	microSD Card Slot	microSD Card Slot	SD Card Slot	microSD Card Slot	
Power	5VDC 3.9W	PoE / 5VDC 6.1W	PoE / 12VDC 10W	PoE / 12VDC 12.5W	PoE / 12VDC 24VAC 10.5W	PoE / 12VDC 10W	12VDC 14W
Positioning	N/A	3-Axis	3-Axis	3-Axis	3-Axis	3-Axis	2-Axis
Outdoor Use	No	Yes (IP65)	Yes (IP68)	Yes (IP68)	Yes (IP67)	Yes (IP67)	No
Other	360° / 180° Wireless N	Compact Vandalproof Cloud-Enabled -13° to 113° F	Weather Guard Vandalproof -22° to 122° F	Weather Guard Vandalproof -22° to 122° F	Weather Guard Vandalproof -40° to 122° F	Weather Guard Vandalproof -40° to 122° F	Endless 360° Pan 400°/Second
Warranty	1-Year	5-Year	5-Year	5-Year	5-Year	5-Year	1-Year
Pricing*	\$\$	\$\$	\$\$	\$\$	\$\$\$	\$\$\$	\$\$\$

*Pricing Legend: Value = \$, Mid-Tier = \$\$, High-End = \$\$\$

Network Video Recorders	Network Video Recorders	
		
	DNR-312L	DNR-322L
Supported IP Cameras	D-Link	D-Link
Channels	9	9
Recording Performance	Up to 270 FPS @ HD	Up to 270 FPS @ HD
Record on Camera Motion Detection	✓	✓
HDD Bays	1 x 3.5" SATA	2 x 3.5" SATA
Max Capacity	6TB	12TB
Network	1x GigE LAN Port	1x GigE LAN Port
Raid Levels	N/A	Single, RAID 0, RAID 1, JBOD
mydlink Cloud Enabled	✓	✓
Supported Compression	H.264 MPEG-4 MJPEG	H.264 MPEG-4 MJPEG
Auto Camera Detection	✓	✓
Mouse In	✓	
Monitor Out	HDMI	
Multiple NVR Management/Viewing Client Software		✓
Pricing	\$	\$

Mounts		
	DCS-34-2	DCS-35-1
Description	Pendant Mount	Flush Mount
Supported Products	DCS-6314, DCS-6315, DCS-6511, DCS-6513, DCS-6517	DCS-6616

Mounts			
	DCS-37-1	DCS-37-2	DCS-37-3
Description	Wall Mount	Ceiling Mount	Angled Ceiling Mount
Supported Products	DCS-4602EV, DCS-4603, DCS-4802E, DCS-6212L	DCS-4602EV, DCS-4603, DCS-4802E, DCS-6212L	DCS-4602EV, DCS-4603, DCS-4802E, DCS-6212L



Each D-Link IP camera includes a free 32-camera VMS solution called D-ViewCam. If your customer's surveillance needs require a more robust, full featured and scalable solution, D-Link has a large number of VMS partners that support D-Link's line of IP cameras.

Virtually all D-Link cameras are ONVIF-compliant, enabling IP cameras, NVRs and VMS solutions from multiple vendors to seamlessly work together.



Call or visit us online for more information on the complete line of D-Link IP Surveillance solutions

ipsurveillance.dlink.com

888.331.8686 | Email: getmore@dlink.com